



PRODUCT SPECIFICATIONS
DOMO Champion Infinity

Patent pending

Application	Football, Multisport	
Fibres	Polyamide / UV-Stabilized / Straight & Curled / 100 % Monofilament - 14.000 dtex ca. 140 µm thickness	
Production Method	Linear Tufting	
Gauge	5/16"	
# stitches / lm	140	± 10%
# tufts / m ²	17.640	± 10%
# filaments / m ²	564.480	± 10%
Pile Height	38 mm	± 5%
Pile Weight	2.200 gr / m ²	± 10%
Total Height	40 mm	± 5%
Total Weight	3.466 gr / m ²	± 10%
Tuft Cloth	Polyester, UV-Stabilized, ca. 266 gr / m ²	± 5%
Backing	Latex, 1.000 gr / m ²	± 10%
Infill	Not required	
Roll Width	400 cm	
Roll Length	Following Layout Plan	
Colour	Green (two shades)	
Colour Lines	White	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 6.000 Hours (DIN 53387)	
Wasser Permeability	6.10 ⁻⁴ m / s	
Inflammability	Class 1 (DIN 51960)	
Pile Anchorage	> 30 N	
Chlor Resistance	4 – 5 (DIN 54019)	
Resistance to sea water	4 – 5 (DIN 54007)	

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.