



PRODUCT SPECIFICATIONS **DOMO Excellence 60**

Patented Product

| | |
|--------------------------|---|
| Applications | Soccer, Rugby |
| Fibre | Polyethylene / UV-stabilized / Straight / Fibrillated & Monofilament 15.000 dtex 9 mm & 6 x 1,4 mm ca. 120 micron |
| Production Method | Linear tufting |
| Gauge | 5/8" |
| # stitches / lm | ca. 110 / lm |
| # tufts / m ² | ca. 6.929 / m ² |
| # piles / m ² | ca. 13.858 / m ² |
| Pile Height | ca. 60 mm |
| Pile Weight | ca. 1.400 gr / m ² |
| Total Height | ca. 62 mm |
| Total Weight | ca. 2.594 gr / m ² |
| Tuft Cloth | Polypropylene, UV-stabilized, ca. 164 gr / m ² Woven Glassfabric, ca. 130 gr / m ² |
| Backing | Latex, ca. 900 gr / m ² |
| Infill | Sand (ca. 20 kg, depending on subbase installed) Rubber (ca. 12 - 17 kg, depending on subbase installed) |
| Roll Width | 400 cm |
| Roll Length | As per lay-out |
| Colour | Green |
| Colour Lines | White / Yellow |
| Colour Fastness | Scale 7 (DIN 54004) |
| UV-Stability | > 6.000 hours (DIN 53387) |
| Water Permeability | 6.10 ⁻⁴ m/sec |
| Inflammability | Class 1 with flame retardant EPDM infill (DIN 51960) |
| Pile Anchorage | > 30 N |
| Test Reports | Labosport / FNCESEL 03-0719-1 (French) Labosport / European Standards 03-0718 (English) Labosport / LND 03-1033 (Italian) Labosport / Lisport 10.000 cycli 04-0952 (French) UEFA / U-084/04/DC-03 (English) Byggforsk / NBI-UEFA 475-0402-Ex-e (English) Labosport / European Standards 05-0041 (English) FIFA 2* |

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.