



## PRODUCT SPECIFICATIONS DOMO Golf Montana

Applications	Golf putting green
Fibre	Polyethylene / UV-stabilized / Straight / Monofilament 8.800 dtex 1,2 mm ca. 120 micron
Production Method	Linear Tufting
Gauge	5/32"
# stitches / lm	ca. 240 / lm
# tufts / m <sup>2</sup>	ca. 50.394 / m <sup>2</sup>
# piles / m <sup>2</sup>	ca. 100.788 / m <sup>2</sup>
Pile Height	ca. 15 mm
Pile Weight	ca. 1.900 gr / m <sup>2</sup>
Total Height	ca. 17 mm
Total Weight	ca. 3.064 gr / m <sup>2</sup>
Tuft Cloth	Polypropylene, UV-stabilized, ca. 164 gr / m <sup>2</sup>
Backing	Latex, ca. 1.000 gr / m <sup>2</sup>
Infill	Sand (ca. 8 kg, depending on subbase installed)
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 <sup>-4</sup> m / sec
Inflammability	Class 1 (DIN 51960)

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.