



PRODUCT SPECIFICATIONS DOMO Parkland TST Collar

Patented Product

Applications	Golf (Collar)
--------------	-----------------

Fibre	Polyethylene / UV-stabilized / Straight / Combination yarn 15.000 dtex Monofilament – ca 160µm thickness
-------	--

Production Method	Linear tufting
Gauge	5/8"
# stitches / lm	110 / lm ± 10%
# tufts / m ²	6.929 / m ² ± 10%
# piles / m ²	97.006 / m ² ± 10%
Pile Height	30 mm ± 5%
Pile Weight	825 gr / m ² ± 10%
Total Height	32 mm ± 5%
Total Weight	2.014 gr / m ² ± 10%
Tuft Cloth	Polypropylene, UV-stabilized, 164 gr / m ² ± 5%
Backing	Latex, 1.000 gr / m ² ± 10%

Infill	Sand (ca. 15 kg/m ²) (>80% roundness)
Fixation infill	Fibrillated yarn 80µm

Roll Width	400 cm
Roll Length	As per lay-out

Colour	Green
Colour Lines	White / Yellow

Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 ⁻⁴ m/s
Inflammability	Class 1 (DIN 51960)
Pile Anchorage	> 30 N

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.