



PRODUCT SPECIFICATIONS DOMO Parkland TST Fairway

Patented Product

Applications	Golf (Fairway / Tee)	
Fibre	Polyethylene / UV-Stabilized / Straight / Monofilament ca 160µm thickness/ 15.000 dtex	
Production Method	Zigzag Tufting	
Gauge	5/8"	
# stitches / lm	150 / lm	± 10%
# tufts / m ²	9.450 / m ²	± 10%
# piles	132.300 /m ²	± 10%
Pile Height	55 mm	± 5%
Pile Weight	1.775 gr / m ²	± 10%
Total Height	57 mm	± 5%
Total Weight	3.069 gr / m ²	± 10%
Tuft Cloth	Polypropylene, UV-Stabilized, 164 gr / m ²	± 5%
	Woven Glassfabric 130 gr/m ²	± 5%
Backing	Latex, 1.000 gr / m ²	± 10%
Infill	Sand (ca 60 kg/m ²) (> 80% roundness)	
Fixation infill	Fibrillated yarn 80µm	
Roll Width	400 cm	
Roll Length	As per lay-out	
Colour	Green	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 6.000 hours (DIN 53387)	
Water Permeability	6.10 ⁻⁴ m/sec	
Pile Anchorage	> 30 N	

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.