



PRODUCT SPECIFICATIONS DOMO Parkland TST Fringe

Patented Product

Applications	Golf (Fringe)
Fibre	Polyethylene / UV-Stabilized / 12.000 dtex / Monofilament / Straight & Curled
Production Method	Multidirectional Tufting
Gauge	5/16"
# stitches / lm	220 / lm $\pm 10\%$
# tufts / m ²	27.720 / m ² $\pm 10\%$
Pile Height	26 mm $\pm 5\%$
Pile Weight	2.000 gr / m ² $\pm 10\%$
Total Height	28 mm $\pm 5\%$
Total Weight	3.164 gr / m ² $\pm 10\%$
Tuft Cloth	Polypropylene, UV-Stabilized, 164 gr / m ² $\pm 5\%$
Backing	Latex, 1.000 gr / m ² $\pm 10\%$
Infill	Sand (ca 10-15 kg/m ²) (>80% roundness)
Colour	Green
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 ⁻⁴ m/sec
Pile Anchorage	> 30 N
Chlore Resistance	4 – 5 (DIN 54019)
Resistance to sea water	4 – 5 (DIN 54007)

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.