



**SPORTS & LEISURE GRASS**

## PRODUCT SPECIFICATIONS DOMO Parkland TST Green

Applications	Golf ( Putting Green)
Fibre	Polyamide / UV-Stabilized / Straight / Monofilament / 5.200 dtex
Production Method	Linear Tufting
Gauge	5/32"
# stitches / lm	290 / lm ± 10%
# tufts / m <sup>2</sup>	73.080 / m <sup>2</sup> ± 10%
# piles	1.169.280 / m <sup>2</sup> ± 10%
Pile Height	15 mm ± 5%
Pile Weight	1.450 gr / m <sup>2</sup> ± 10%
Total Height	17 mm ± 5%
Total Weight	2.716 gr / m <sup>2</sup> ± 10%
Tuft Cloth	Polyester - Polypropylene, UV-Stabilized, 164 gr / m <sup>2</sup> ± 5%
Backing	Latex, 1.000 gr / m <sup>2</sup> ± 10%
Infill	Sand ( ca 8 kg/m <sup>2</sup> ) (> 80% roundness)
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 <sup>-4</sup> m/sec
Pile Anchorage	> 30 N

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.