



PRODUCT SPECIFICATIONS DOMO Parkland TST Rough

Applications	Golf (Rough)	
Fibre	Polyethylene / UV-Stabilized / Straight / Monofilament ca 165µm thickness/ 15.000 dtex	
Production Method	Linear Tufting	
Gauge	5/8"	
# stitches / lm	110 / lm	± 10%
# tufts / m ²	6.929 / m ²	± 10%
# piles	97.006 /m ²	± 10%
Pile Height	70 mm	± 5%
Pile Weight	1.635 gr / m ²	± 10%
Total Height	72 mm	± 5%
Total Weight	3.029 gr / m ²	± 10%
Tuft Cloth	Polypropylene, UV-Stabilized, 164 gr / m ² Woven Glassfabric 130 gr/m ²	± 5% ± 5%
Backing	Latex, 1.100 gr / m ²	± 10%
Infill	Sand (ca 30 kg/m ²) (> 80% roundness)	
Fixation infill	Fibrillated yarn 80µm	
Roll Width	400 cm	
Roll Length	As per lay-out	
Colour	Green	
Colour Fastness	Scale 7 (DIN 54004)	
UV-Stability	> 6.000 hours (DIN 53387)	
Water Permeability	6.10 ⁻⁴ m/sec	
Pile Anchorage	> 30 N	

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.