



PRODUCT SPECIFICATIONS DOMO PRO MAT

Applications	Golf ; Driving Mat		
Fibre	100% Polyamide / UV-stabilized / Curled / Monofilament 5200 dtex 8 monofilaments		
Production Method	Tufting		
Gauge	5/32"		
# stitches / lm	ca. 340 / lm		± 10%
# tufts / m ²	ca. 85.680 / m ²		± 10%
# piles / m ²	ca. 685.440 / m ²		± 10%
Pile Height	ca. 15 mm		± 5%
Pile Weight	ca. 1.700 gr / m ²		± 10%
Total Height	ca. 37 mm		± 5%
Total Weight	ca. 18.466 gr / m ²		± 10%
Tuft Cloth	Polyester, UV-stabilized, ca. 266 gr / m ²		± 5%
Backing	Latex, ca. 1.000 gr / m ²		± 10%
Underlay	Elastic layer of SBR rubber 20mm thickness weight:14.500g/m ²		
Glue	Based on PU (waterresistant)		
Dimensions	130cm X 130cm		
Tee holes	Rubber tee = 4 pieces (diameter 18mm)		
	Wooden tee= 4 pieces (cut of 5 cm)		
Colour	Green		
Colour Fastness	Scale 7 (DIN 54004)		
UV-Stability	> 6.000 hours (DIN 53387)		
Pile Anchorage	> 30 N		

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.