



PRODUCT SPECIFICATIONS DOMO Serve

Applications	Tennis, Paddle, Multisports
--------------	-----------------------------

Fibre	Polypropylene / UV-stabilized / Straight / Fibrillated 6.600 dtex ca. 60µm thickness
-------	--

Production Method	Linear tufting
Gauge	5/16"
# stitches / lm	160 / lm ± 10%
# tufts / m ²	20.160 / m ² ± 10%
# piles / m ²	40.320 / m ² ± 10%
Pile Height	15 mm ± 5%
Pile Weight	525 gr / m ² ± 10%
Total Height	17 mm ± 5%
Total Weight	1.460 gr / m ² ± 10%
Tuft Cloth	Polypropylene, UV-stabilized, 134 gr / m ² ± 5%
Backing	Latex, 800 gr / m ² ± 10%

Infill	Sand (ca. 15 kg) (> 80% roundness)
--------	------------------------------------

Roll Width	370 or 400 cm
Roll Length	As per lay-out

Colour	Green / Red
Colour Lines	White / Yellow

Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	> 6. 10 ⁻⁴ m/sec
Inflammability	Class 1 (DIN 51960)
Pile Anchorage	> 30N

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.